Introduction to NLP

CSE5321/CSEG321

Lecture 8. LSTM RNNs and Neural Machine Translation
Hwaran Lee (hwaranlee@sogang.ac.kr)

Lecture Plan

Lecture 8: LSTM RNNs and Neural Machine Translation

- 1. Exploding and vanishing gradients
- 2. Long Short-Term Memory Networks (LSTMs)
- 3. Other uses of RNNs
- 4. Bidirectional and multi-layer RNNs
- 5. Intro to Machine Translation and Sequence-to-sequence models (if time permits)


Key Goal: Understanding RNN variants.

Recap


- Language Model: A system that predicts the next word
- Recurrent Neural Network: A family of neural networks that:
 - Take sequential input of any length; apply the same weights on each step
 - Can optionally produce output on each step
- Recurrent Neural Network ≠ Language Model
 - RNNs can be used for many other things (see later)
- Language Modeling is a traditional subcomponent of many NLP tasks, all those involving generating text or estimating the probability of text:
 - Now everything in NLP is being rebuilt upon Language Modeling: GPT-3 is an LM!

Generating with an RNN Language Model ("Generating roll outs")

Just like an n-gram Language Model, you can use a RNN Language Model to generate text by repeated sampling. Sampled output becomes next step's input.



Training the parameters of RNNs: Backpropagation for RNNs



In practice, often
"truncated" after ~20
timesteps for training
efficiency reasons


Question: How do we calculate this?


Answer: Backpropagate over timesteps i = t, ..., 0, summing gradients as you go. This algorithm is called "backpropagation through time" [Werbos, P.G., 1988, Neural Networks 1, and others]


Apply the multivariable chain rule:

$$egin{align} rac{\partial J^{(t)}}{\partial oldsymbol{W}_h} &= \sum_{i=1}^t rac{\partial J^{(t)}}{\partial oldsymbol{W}_h} igg|_{(i)} rac{\partial oldsymbol{W}_h igg|_{(i)}}{\partial oldsymbol{W}_h} \ &= \sum_{i=1}^t rac{\partial J^{(t)}}{\partial oldsymbol{W}_h} igg|_{(i)} \ \end{split}$$


3. Problems with RNNs: Vanishing and Exploding Gradients









chain rule!



chain rule!



chain rule!



Vanishing gradient proof sketch (linear case)

Recall:

$$oldsymbol{h}^{(t)} = \sigma \left(oldsymbol{W}_h oldsymbol{h}^{(t-1)} + oldsymbol{W}_x oldsymbol{x}^{(t)} + oldsymbol{b}_1
ight)$$

• What if σ were the identity function, $\sigma(x) = x$?

$$egin{aligned} rac{\partial m{h}^{(t)}}{\partial m{h}^{(t-1)}} &= \mathrm{diag}\left(\sigma'\left(m{W}_hm{h}^{(t-1)} + m{W}_xm{x}^{(t)} + m{b}_1
ight)
ight)m{W}_h & \qquad ext{(chain rule)} \ &= m{I} \,\,m{W}_h = \,m{W}_h \end{aligned}$$

• Consider the gradient of the loss $J^{(i)}(\theta)$ on step i, with respect to the hidden state $m{h}^{(j)}$ on some previous step j. Let $\ell=i-j$

$$\frac{\partial J^{(i)}(\theta)}{\partial \boldsymbol{h}^{(j)}} = \frac{\partial J^{(i)}(\theta)}{\partial \boldsymbol{h}^{(i)}} \prod_{j < t \le i} \frac{\partial \boldsymbol{h}^{(t)}}{\partial \boldsymbol{h}^{(t-1)}} \qquad \text{(chain rule)}$$

$$= \frac{\partial J^{(i)}(\theta)}{\partial \boldsymbol{h}^{(i)}} \prod_{j < t \le i} \boldsymbol{W}_h = \frac{\partial J^{(i)}(\theta)}{\partial \boldsymbol{h}^{(i)}} \boldsymbol{W}_h^{\ell} \qquad \text{(value of } \frac{\partial \boldsymbol{h}^{(t)}}{\partial \boldsymbol{h}^{(t-1)}} \text{)}$$

If W_h is "small", then this term gets exponentially problematic as ℓ becomes large

Vanishing gradient proof sketch (linear case)

- What's wrong with W_h^ℓ ?
- Consider if the eigenvalues of W_h are all less than 1:

$$\lambda_1, \lambda_2, \dots, \lambda_n < 1$$
 q_1, q_2, \dots, q_n (eigenvectors)

• We can write $\frac{\partial J^{(i)}(\theta)}{\partial \boldsymbol{h}^{(i)}} \, \boldsymbol{W}_h^\ell$ using the eigenvectors of \boldsymbol{W}_h as a basis:

$$\frac{\partial J^{(i)}(\theta)}{\partial \boldsymbol{h}^{(i)}} \boldsymbol{W}_h^{\ell} = \sum_{i=1}^n c_i \lambda_i^{\ell} \boldsymbol{q}_i \approx \boldsymbol{0} \text{ (for large } \ell)$$


Approaches 0 as ℓ grows, so gradient vanishes

sufficient but

not necessary

- What about nonlinear activations σ (i.e., what we use?)
 - Pretty much the same thing, except the proof requires $\lambda_i < \gamma$ for some γ dependent on dimensionality and σ

Why is vanishing gradient a problem?



Gradient signal from far away is lost because it's much smaller than gradient signal from close-by.

So, model weights are updated only with respect to near effects, not long-term effects.

Effect of vanishing gradient on RNN-LM

- LM task: When she tried to print her tickets, she found that the printer was out of toner.
 She went to the stationery store to buy more toner. It was very overpriced. After installing the toner into the printer, she finally printed her ______
- To learn from this training example, the RNN-LM needs to model the dependency between "tickets" on the 7th step and the target word "tickets" at the end.
- But if the gradient is small, the model can't learn this dependency
 - So, the model is unable to predict similar long-distance dependencies at test time

Why is exploding gradient a problem?

If the gradient becomes too big, then the SGD update step becomes too big:

$$\theta^{new} = \theta^{old} - \alpha \nabla_{\theta} J(\theta)$$
 gradient

- This can cause bad updates: we take too large a step and reach a weird and bad parameter configuration (with large loss)
 - You think you've found a hill to climb, but suddenly you're in Iowa
- In the worst case, this will result in Inf or NaN in your network (then you have to restart training from an earlier checkpoint)

Gradient clipping: solution for exploding gradient

 Gradient clipping: if the norm of the gradient is greater than some threshold, scale it down before applying SGD update

Algorithm 1 Pseudo-code for norm clipping
$$\hat{\mathbf{g}} \leftarrow \frac{\partial \mathcal{E}}{\partial \theta}$$
 if $\|\hat{\mathbf{g}}\| \geq threshold$ then
$$\hat{\mathbf{g}} \leftarrow \frac{threshold}{\|\hat{\mathbf{g}}\|} \hat{\mathbf{g}}$$
 end if

- Intuition: take a step in the same direction, but a smaller step
- In practice, remembering to clip gradients is important, but exploding gradients are an easy problem to solve


How to fix the vanishing gradient problem?

- The main problem is that it's too difficult for the RNN to learn to preserve information over many timesteps.
- In a vanilla RNN, the hidden state is constantly being rewritten

$$oldsymbol{h}^{(t)} = \sigma \left(oldsymbol{W}_h oldsymbol{h}^{(t-1)} + oldsymbol{W}_x oldsymbol{x}^{(t)} + oldsymbol{b}
ight)$$

- First off next time: How about an RNN with separate memory which is added to?
 - LSTMs
- And then: Creating more direct and linear pass-through connections in model
 - Attention, residual connections, etc.

Our starting point: vanishing gradients



Long Short-Term Memory RNNs (LSTMs)

- A type of RNN proposed by Hochreiter and Schmidhuber in 1997 as a solution to the problem of vanishing gradients
 - Everyone cites that paper but really a crucial part of the modern LSTM is from Gers et al. (2000)



- Only started to be recognized as promising through the work of S's student Alex Graves c. 2006
 - Work in which he also invented CTC (connectionist temporal classification) for speech recognition
- But only really became well-known after Hinton brought it to Google in 2013
 - Following Graves having been a postdoc with Hinton

Long Short-Term Memory RNNs (LSTMs)

- On step t, there is a hidden state $\boldsymbol{h}^{(t)}$ and a cell state $\boldsymbol{c}^{(t)}$
 - Both are vectors length *n*
 - The cell stores long-term information
 - The LSTM can read, erase, and write information from the cell
 - The cell becomes conceptually rather like RAM in a computer
- The selection of which information is erased/written/read is controlled by three corresponding gates
 - The gates are also vectors of length n
 - On each timestep, each element of the gates can be open (1), closed (0), or somewhere in-between
 - The gates are dynamic: their value is computed based on the current context

Long Short-Term Memory (LSTM)

We have a sequence of inputs $x^{(t)}$, and we will compute a sequence of hidden states $h^{(t)}$ and cell states $c^{(t)}$. On timestep t:

> Forget gate: controls what is kept vs forgotten, from previous cell state

Input gate: controls what parts of the new cell content are written to cell

Output gate: controls what parts of cell are output to hidden state

New cell content: this is the new content to be written to the cell

Cell state: erase ("forget") some content from last cell state, and write ("input") some new cell content

<u>Hidden state</u>: read ("output") some content from the cell

Sigmoid function: all gate values are between 0 and 1

$$egin{aligned} oldsymbol{f}^{(t)} &= \sigma \left(oldsymbol{W}_f oldsymbol{h}^{(t-1)} + oldsymbol{U}_f oldsymbol{x}^{(t)} + oldsymbol{b}_f
ight) \ oldsymbol{i}^{(t)} &= \sigma \left(oldsymbol{W}_i oldsymbol{h}^{(t-1)} + oldsymbol{U}_i oldsymbol{x}^{(t)} + oldsymbol{b}_i
ight) \ oldsymbol{o}^{(t)} &= \sigma \left(oldsymbol{W}_o oldsymbol{h}^{(t-1)} + oldsymbol{U}_o oldsymbol{x}^{(t)} + oldsymbol{b}_o
ight) \end{aligned}$$

$$oldsymbol{i}^{(t)} = \sigma \left(oldsymbol{W}_i oldsymbol{h}^{(t-1)} + oldsymbol{U}_i oldsymbol{x}^{(t)} + oldsymbol{b}_i
ight)$$

$$oldsymbol{o}^{(t)} = \sigma \left(oldsymbol{W}_o oldsymbol{h}^{(t-1)} + oldsymbol{U}_o oldsymbol{x}^{(t)} + oldsymbol{b}_o
ight)$$

$$egin{aligned} oldsymbol{ ilde{c}} & ilde{oldsymbol{c}}^{(t)} = anh\left(oldsymbol{W}_coldsymbol{h}^{(t-1)} + oldsymbol{U}_coldsymbol{x}^{(t)} + oldsymbol{b}_c
ight) \ oldsymbol{c}^{(t)} = oldsymbol{f}^{(t)} \circ oldsymbol{c}^{(t-1)} + oldsymbol{i}^{(t)} \circ ilde{oldsymbol{c}}^{(t)} \end{aligned}$$


$$ightharpoonup oldsymbol{h}^{(t)} = oldsymbol{o}^{(t)} \circ anh oldsymbol{c}^{(t)}$$


Gates are applied using element-wise (or Hadamard) product: ⊙

All these are vectors of same length $\it n$

Long Short-Term Memory (LSTM)


You can think of the LSTM equations visually like this:





Long Short-Term Memory (LSTM)

You can think of the LSTM equations visually like this:



How does LSTM solve vanishing gradients?


- The LSTM architecture makes it much easier for an RNN to preserve information over many timesteps
 - e.g., if the forget gate is set to 1 for a cell dimension and the input gate set to 0, then the information of that cell is preserved indefinitely.
 - In contrast, it's harder for a vanilla RNN to learn a recurrent weight matrix W_h that preserves info in the hidden state
 - In practice, you get about 100 timesteps rather than about 7
- However, there are alternative ways of creating more direct and linear pass-through connections in models for long distance dependencies

Is vanishing/exploding gradient just an RNN problem?

- No! It can be a problem for all neural architectures (including feed-forward and convolutional), especially very deep ones.
 - Due to chain rule / choice of nonlinearity function, gradient can become vanishingly small as it backpropagates
 - Thus, lower layers are learned very slowly (i.e., are hard to train)
- Another solution: lots of new deep feedforward/convolutional architectures add more direct connections (thus allowing the gradient to flow)

For example:


- Residual connections aka "ResNet"
- Also known as skip-connections
- The identity connection preserves information by default
- This makes deep networks much easier to train



Is vanishing/exploding gradient just a RNN problem?


Other methods:

- Dense connections aka "DenseNet"
- Directly connect each layer to all future layers!



Highway connections aka "HighwayNet"

- Similar to residual connections, but the identity connection vs the transformation layer is controlled by a dynamic gate
- Inspired by LSTMs, but applied to deep feedforward/convolutional networks



• **Conclusion**: Though vanishing/exploding gradients are a general problem, RNNs are particularly unstable due to the repeated multiplication by the same weight matrix [Bengio et al, 1994]

[&]quot;Densely Connected Convolutional Networks", Huang et al, 2017. https://arxiv.org/pdf/1608.06993.pdf


[&]quot;Highway Networks", Srivastava et al, 2015. https://arxiv.org/pdf/1505.00387.pdf


LSTMs: real-world success

- In 2013–2015, LSTMs started achieving state-of-the-art results
 - Successful tasks include handwriting recognition, speech recognition, machine translation, parsing, and image captioning, as well as language models
 - LSTMs became the dominant approach for most NLP tasks
- Recently (2019–2024), Transformers have become dominant for all tasks
 - For example, in **WMT** (a Machine Translation conference + competition):
 - In WMT 2014, there were 0 neural machine translation systems (!)
 - In WMT 2016, the summary report contains "RNN" 44 times (and these systems won)
 - In WMT 2019: "RNN" 7 times, "Transformer" 105 times
- Now, 'State space models' (RNN++) are making a comeback

4. Bidirectional and Multi-layer RNNs: motivation

Task: Sentiment Classification





Bidirectional RNNs


On timestep *t*:

This is a general notation to mean "compute one forward step of the RNN" – it could be a simple RNN or LSTM computation.

Forward RNN
$$\overrightarrow{\boldsymbol{h}}^{(t)} = \overline{\text{RNN}_{\text{FW}}}(\overrightarrow{\boldsymbol{h}}^{(t-1)}, \boldsymbol{x}^{(t)})$$
 Generally, these two RNNs have separate weights
$$\overleftarrow{\boldsymbol{h}}^{(t)} = \overline{\text{RNN}_{\text{BW}}}(\overleftarrow{\boldsymbol{h}}^{(t+1)}, \boldsymbol{x}^{(t)})$$
 Concatenated hidden states
$$\overleftarrow{\boldsymbol{h}}^{(t)} = [\overrightarrow{\boldsymbol{h}}^{(t)}; \overleftarrow{\boldsymbol{h}}^{(t)}]$$

We regard this as "the hidden state" of a bidirectional RNN.
This is what we pass on to the next parts of the network.

Bidirectional RNNs: simplified diagram



The two-way arrows indicate bidirectionality and the depicted hidden states are assumed to be the concatenated forwards+backwards states

Bidirectional RNNs

- Note: bidirectional RNNs are only applicable if you have access to the entire input sequence
 - They are not applicable to Language Modeling, because in LM you only have left context available.
- If you do have entire input sequence (e.g., any kind of encoding), bidirectionality is powerful (you should use it by default).
- For example, BERT (Bidirectional Encoder Representations from Transformers) is a
 powerful pretrained contextual representation system built on bidirectionality.
 - You will learn more about transformers, including BERT, in a couple of weeks!


Multi-layer RNNs

- RNNs are already "deep" on one dimension (they unroll over many timesteps)
- We can also make them "deep" in another dimension by applying multiple RNNs – this is a multi-layer RNN.
- This allows the network to compute more complex representations
 - The lower RNNs should compute lower-level features and the higher RNNs should compute higher-level features.
- Multi-layer RNNs are also called stacked RNNs.



Multi-layer RNNs

The hidden states from RNN layer *i* are the inputs to RNN layer *i*+1



Multi-layer RNNs in practice

- Multi-layer or stacked RNNs allow a network to compute more complex representations
 - they work better than just have one layer of high-dimensional encodings!
 - The lower RNNs should compute lower-level features and the higher RNNs should compute higher-level features.
- High-performing RNNs are usually multi-layer (but aren't as deep as convolutional or feed-forward networks)
- For example: In a 2017 paper, Britz et al. find that for Neural Machine Translation, 2 to 4 layers is best for the encoder RNN, and 4 layers is best for the decoder RNN
 - Often 2 layers is a lot better than 1, and 3 might be a little better than 2
 - Usually, skip-connections/dense-connections are needed to train deeper RNNs (e.g., 8 layers)
- Transformer-based networks (e.g., BERT) are usually deeper, like 12 or 24 layers.
 - You will learn about Transformers later; they have a lot of skipping-like connections

Machine Translation

Machine Translation (MT) is the task of translating a sentence x from one language (the source language) to a sentence y in another language (the target language).

x: L'homme est né libre, et partout il est dans les fers

y: Man is born free, but everywhere he is in chains

- Rousseau

The early history of MT: 1950s

- Machine translation research began in the early 1950s on machines less powerful than high school calculators (before term "A.I." coined!)
- Concurrent with foundational work on automata, formal languages, probabilities, and information theory
- MT heavily funded by military, but basically just simple rule-based systems doing word substitution
- Human language is more complicated than that, and varies more across languages!
- Little understanding of natural language syntax, semantics, pragmatics
- Problem soon appeared intractable

1 minute video showing 1954 MT:

https://youtu.be/K-HfpsHPmvw

The early history of MT: 1950s



1990s-2010s: Statistical Machine Translation

- Core idea: Learn a probabilistic model from data
- Suppose we're translating French → English.
- We want to find best English sentence y, given French sentence x

$$\operatorname{argmax}_{y} P(y|x)$$

 Use Bayes Rule to break this down into two components to be learned separately:

$$= \operatorname{argmax}_{y} P(x|y) P(y)$$

Translation Model

Models how words and phrases should be translated (fidelity).

Learned from parallel data.

Language Model

Models how to write good English (fluency).
Learned from monolingual data.

1990s-2010s: Statistical Machine Translation

- SMT was a huge research field
- The best systems were extremely complex
 - Hundreds of important details
- Systems had many separately-designed subcomponents
 - Lots of feature engineering
 - Need to design features to capture particular language phenomena
 - Required compiling and maintaining extra resources
 - Like tables of equivalent phrases
 - Lots of human effort to maintain
 - Repeated effort for each language pair!



NMT: the first big success story of NLP Deep Learning

Neural Machine Translation went from a fringe research attempt in **2014** to the leading standard method in 2016

- **2014**: First seq2seq paper published [Sutskever et al. 2014]
- **2016**: Google Translate switches from SMT to NMT and by 2018 everyone has


















- This is amazing!
 - SMT systems, built by hundreds of engineers over many years, outperformed by NMT systems trained by small groups of engineers in a few months

Neural Machine Translation (NMT)

The sequence-to-sequence model



Encoder RNN produces an encoding of the source sentence.

Decoder RNN is a Language Model that generates target sentence, conditioned on encoding.

Note: This diagram shows **test time** behavior: decoder output is fed in ······→ as next step's input

Sequence-to-sequence is versatile!

- The general notion here is an encoder-decoder model
 - One neural network takes input and produces a neural representation
 - Another network produces output based on that neural representation
 - If the input and output are sequences, we call it a seq2seq model
- Sequence-to-sequence is useful for more than just MT
- Many NLP tasks can be phrased as sequence-to-sequence:
 - Summarization (long text → short text)
 - Dialogue (previous utterances → next utterance)
 - Parsing (input text → output parse as sequence)
 - Code generation (natural language → Python code)

Neural Machine Translation (NMT)

- The sequence-to-sequence model is an example of a Conditional Language Model
 - Language Model because the decoder is predicting the next word of the target sentence y
 - Conditional because its predictions are also conditioned on the source sentence x


• NMT directly calculates P(y|x):

$$P(y|x) = P(y_1|x) P(y_2|y_1, x) P(y_3|y_1, y_2, x) \dots P(y_T|y_1, \dots, y_{T-1}, x)$$

Probability of next target word, given target words so far and source sentence *x*

- Question: How to train an NMT system?
- (Easy) Answer: Get a big parallel corpus...
 - But there is now exciting work on "unsupervised NMT", data augmentation, etc.

Training a Neural Machine Translation system




Seq2seq is optimized as a **single system**. Backpropagation operates "end-to-end".

Multi-layer deep encoder-decoder machine translation net


[Sutskever et al. 2014; Luong et al. 2015]

The hidden states from RNN layer *i* are the inputs to RNN layer *i*+1



Conditioning = Bottleneck


The final piece: the bottleneck problem in RNNs



Problems with this architecture?

Issues with recurrent models: Linear interaction distance


- O(sequence length) steps for distant word pairs to interact means:
 - Hard to learn long-distance dependencies (because gradient problems!)
 - Linear order of words is "baked in"; we already know linear order isn't the right way to think about sentences...



Info of *chef* has gone through O(sequence length) many layers!

Issues with recurrent models: Lack of parallelizability

- Forward and backward passes have O(sequence length) unparallelizable operations
 - GPUs can perform a bunch of independent computations at once!
 - But future RNN hidden states can't be computed in full before past RNN hidden states have been computed
 - Inhibits training on very large datasets!



Numbers indicate min # of steps before a state can be computed